

6050-200 Mesh Degreaser

Technical Data Sheet

Page 1/1

Mesh Degreaser 6050-200 is a ready to use screen mesh cleaner and degreaser for all types of mesh. It is formulated to optimize adhesion, extend stencil life and prepare mesh prior to stencil production. It is used before each application of direct emulsions and direct/indirect stencils.

- Thoroughly degreases and evenly wets all mesh fabrics.
- Prevents pinholes by removing dust particles imparting anti-static properties to the mesh.
- Greatly assists the flow characteristics of direct emulsions.

Physical Data:

Colour:	Brown
Consistency:	Liquid
Viscosity:	6-14 Poise (Spindle 3, Speed 10)
Shelf Life:	1 year at 20°C, 68°F
pH Value:	3.0-4.0

Instructions For Use

1. Wet the screen with cold water.
2. Apply Mesh Degreaser onto both sides of the mesh with soft brush or sponge, rubbing in a circular motion. Ensure that it is distributed equally over the screen.
3. Leave the screen to stand for a few minutes.
4. Wash or hose off with cold water until the effluent is free of foam.
5. Dry as usual prior to applying stencils.

Note: It is recommended that if possible, degrease the screen shortly before it is coated in order to eliminate contamination of the clean screen.

Handling and Storage

- It is recommended to wear suitable protective goggles and gloves. Take particular care to avoid splashes into the eyes and skin contact. If this does occur, rinse immediately with plenty of water. In case of splashes into the eyes, seek medical advice. Wear suitable protective clothing, gloves and eye/face protection.
- Comprehensive information on the safety and handling of Mesh Degreaser 6050-200 is given in the appropriate Smiley Material Safety Data Sheet (MSDS), which are available upon request.
- Mesh Degreaser should be stored in a cool dry area away from heat, light and organic matters (food drinks, etc.). Containers should be tightly closed immediately after use.

Environmental Information

This product is not considered hazardous in general.

Additional Information

For additional product information, please visit our website at www.smiley.co.th. For further information, please contact SPS personnel at CRM@smiley.co.th.

Thank you for choosing **SMILEY**.

PRODUCT OFFERING:

Packaging:

6050-200 is available in 1 kilo, 5 kilos and 20 kilos containers.

Smiley Printing Solution Co., Ltd. (SPS), abides by the quality of this product. The information and recommendations that embody this Technical Data Sheet along with the technical advice are based solely on our knowledge and therefore confident to be precise. This product has been specifically formulated for screen printing. SPS cannot guarantee the precision for other possible application for the reason that manufacturing methods and other materials vary. Any liability amalgamated with the use and application of these products, users are the sole bearer of responsibility for choosing appropriate product for end-users' requirement. This Technical Data Sheet is provided for the technical purpose in the usage of this product and users are expected to follow current recommendation.

20/22 Moo 4 Theparak Rd., Bangpre Yai, Bangpre, Samutprakarn 10540, Thailand.

TEL : 662-757-4769, 662-757-4729 FAX : 662-757-4769

www.smiley.co.th ■ e-mail: CRM@smiley.co.th

6050-200-0409012